NSN 5365-01-221-1981

Steel, corrosion resisting

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-221-1981

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Width: |
| 0.125 inches |
| Overall Length: |
| 0.640 inches |
| Thread Size: |
| 1.000-16 |
| Bore Diameter: |
| 0.740 inches |
| Depth: |
| 0.120 inches |
| End Application: |
| Augmentor, fuel control |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Unj |
| Drive Type: |
| Slotted face |
| Thread Location: |
| Both ends |
| Accommodation Type And Quantity: |
| 4 slots |
| Angle Between Accommodations In Deg: |
| 90.0 |
| Beveled Thread: |
| Included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Any acceptable |
| Special Features: |
| Drive end cbored; 0.790 in. Dia, 0.200 in. Dp; has 8 eql spaced holes through wall, placed between slots 0.0465 in. Dia |
| Material: |

NSN 5365-01-221-1981

Externally Threaded Ring - Page 2 of 2



| ΝЛ | ate | ria | |
|-----|-----|------|-----|
| IVI | ale | :110 | II. |

Stainless steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d