## NSN 5365-01-221-1981

Steel, corrosion resisting

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-221-1981

Thread Class:
3a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.125 inches
Overall Length:
0.640 inches
Thread Size:
1.000-16
Bore Diameter:
0.740 inches
Depth:
0.120 inches
End Application:
Augmentor, fuel control
Bore Shape:
Straight
Screw Thread Series Designator:
Unj
Drive Type:
Slotted face
Thread Location:
Both ends
Accommodation Type And Quantity:
4 slots
Angle Between Accommodations In Deg:
90.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Any acceptable
Special Features:
Drive end cbored; 0.790 in. Dia, 0.200 in. Dp; has 8 eql spaced holes through wall, placed between slots 0.0465 in. Dia
Material:

## NSN 5365-01-221-1981

Externally Threaded Ring - Page 2 of 2



ΝЛ	ate	ria	
IVI	ale	:110	II.

Stainless steel

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d