NSN 5365-01-225-4141

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-225-4141 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 30.0 and 45.0 **Chamfer Length:** 0.090 inches and 0.030 inches Width: Between 0.750 inches and 0.760 inches **Overall Length:** 1.080 inches **Thread Size:** 14.250-6 **Bore Diameter:** 12.810 inches Depth: 0.220 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** 12 slots Angle Between Accommodations In Deg: 30.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Drive end and end opposite drive end

Special Features:

0.250 in. By 45.0 degrees chamfer on od end opposite drive end; 1 hole each slot, 0.250-28 unf-2b, placed on 13.600 bc dia

NSN 5365-01-225-4141

Externally Threaded Ring - Page 2 of 2



Material:
Steel, mil-s-5000, comp 4340
Material:
Steel comp 4340
Surface Treatment:
Cadmium
Surface Treatment:
Cadmium, qq-p-416, type 1, class 2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d