

View Online at <https://aerobasegroup.com/nsn/5365-01-226-6304>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

Between 0.125 inches and 0.130 inches

**Overall Length:**

0.400 inches

**Thread Size:**

0.9375-20

**Bore Diameter:**

Between 0.875 inches and 0.880 inches

**Depth:**

0.140 inches

**End Application:**

Valve, p/n 1fa130004-1

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unjef

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 38.0 rockwell c and 41.0 rockwell c

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

4 holes, 0.032 in. Dia, drilled perpendicular to axis, 45.0 degrees apart

**Material:**

Steel, ams 5659

**Material:**

Steel comp xm-12

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated, mil-s-5002

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d