Externally Threaded Ring - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5365-01-226-6304

Thread Class:
3a
Thread Direction:
Right-hand
-
Casehardening Indicator: Not casehardened
Width:
Between 0.125 inches and 0.130 inches
Overall Length:
0.400 inches
Thread Size:
0.9375-20
Bore Diameter:
Between 0.875 inches and 0.880 inches
Depth:
0.140 inches
End Application:
Valve, p/n 1fa130004-1
Bore Shape:
Straight
Screw Thread Series Designator:
Unjef
Drive Type:
Slotted face
Material Hardness Rating:
Between 38.0 rockwell c and 41.0 rockwell c
Accommodation Type And Quantity:
4 slots
Angle Between Accommodations In Deg:
90.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
4 holes, 0.032 in. Dia, drilled perpendicular to axis, 45.0 degrees apart
Material:
Steel, ams 5659
Material:
Steel comp xm-12

## NSN 5365-01-226-6304

Externally Threaded Ring - Page 2 of 2

Surface Treatment:

Passivate

## Surface Treatment:

Passivated, mil-s-5002

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

T252-d

