## NSN 5365-01-226-6304

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-226-6304 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.125 inches and 0.130 inches **Overall Length:** 0.400 inches **Thread Size:** 0.9375-20 **Bore Diameter:** Between 0.875 inches and 0.880 inches Depth: 0.140 inches **End Application:** Valve, p/n 1fa130004-1 Bore Shape: Straight **Screw Thread Series Designator:** Unjef **Drive Type:** Slotted face **Material Hardness Rating:** Between 38.0 rockwell c and 41.0 rockwell c **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 4 holes, 0.032 in. Dia, drilled perpendicular to axis, 45.0 degrees apart Material: Steel, ams 5659 Material:

Steel comp xm-12

## NSN 5365-01-226-6304

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivate

**Surface Treatment:** 

Passivated, mil-s-5002

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d