## NSN 5365-01-230-0163

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-230-0163 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.125 inches **Overall Length:** Between 0.357 inches and 0.359 inches **Taper Minor Diameter:** Between 1.408 inches and 1.409 inches **Taper Major Diameter:** Between 1.536 inches and 1.537 inches **Thread Size:** 1.750-20 Depth: 0.125 inches **Bore Shape: Tapered Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Taper Major Diameter Location:** Opposite drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 1 pellet, p/n e39647-01, 0.120-0.123 in. Diameter x 0.124-0.126 in., inserted on od Material: Steel, ams 5643, cond h1025 or steel, ams 5643, 17-4ph Material:

Steel comp 630 or steel comp 630

## NSN 5365-01-230-0163

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d