Machine Thread Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-230-4040

| ٦ | Thread Direction:                                 |
|---|---|
| F | Right-hand  |
| C | Overall Length:                                   |
| 6 | 69.000 millimeters                                |
| ٦ | Thickness:  |
| ę | 0.500 millimeters                                 |
| ۱ | Nrenching Facility Shape:                         |
| ŀ | Hexagon   |
| ŝ | Screw Thread Length:                              |
| 1 | 0.000 millimeters                                 |
| ١ | Nidth Across Flats:                               |
| E | Between 18.670 millimeters and 19.000 millimeters |
| ł | Hole Inside Diameter:                             |
| E | Between 9.000 millimeters and 9.090 millimeters   |
| Ś | Special Features:                                 |
|   | thread size: 16x1.5                               |
|   | Material:   |
| ( | Copper alloy                                      |
|   | Material Specification:                           |
| ( | Cda, alloy 624 mfr ref single material response   |
| ٦ | Thread Series Designator:                         |
| I | so m  |
| Ś | Shelf Life:                                       |
| ١ | N/a   |
| ι | Jnit Of Measure:                                  |
| - | -   |
| [ | Demilitarization:                                 |
| ١ | No  |
| F | Filg:   |
| ł | A540s0  |