## NSN 5365-01-230-5289

Nonmetallic Bushing - Page 1 of 1

Mil-std-417 spec.



View Online at https://aerobasegroup.com/nsn/5365-01-230-5289

| Nonmetallic Hardness Rating:   |
|--|
| 75.0 shore durometer a and 85.0 shore durometer a  |
| Overall Length:  |
| 1.375 inches   |
| Flange Diameter:   |
| 2.310 inches   |
| Body Diameter:   |
| Between 1.000 inches and 1.010 inches  |
| Body Length:   |
| 0.375 inches   |
| Center Hole Diameter:  |
| Between 0.557 inches and 0.567 inches  |
| Flange Height:   |
| 1.000 inches   |
| Design Type:   |
| Single centrally located hole  |
| Corner Radius Between Flange And Body:   |
| Between 0.010 inches and 0.040 inches  |
| Material:  |
| Rubber chloroprene class cr  |
| Material Specification:  |
| Mil-std-417, type s, class sc, grade sc815abce3f1 military standard single material response |
| Style Designator:  |
| Round flanged  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A535j0   |
| Mil-std (military Standard):   |