NSN 5365-01-236-2114

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-236-2114 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 45.0 **Overall Length:** 1.790 inches Thickness: 0.440 inches **Wrenching Facility Shape:** Hexagon **Countersink Depth:** 0.077 inches **Screw Thread Length:** 1.000 inches Width Across Flats: Between 1.859 inches and 1.906 inches **Countersink Location:** Wrenching end **Hole Inside Diameter:** Between 0.718 inches and 0.875 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): **Thread Size:** 1.250 inches Material: Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1117 or steel comp 1118 **Material Specification:** Astm a576, grade 1010, 1012, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023 or 1025 assn standard single material response or astm a108, grade 1117 or 1118 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5365-01-236-2114

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0