NSN 5365-01-246-4093

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-246-4093 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.081 inches **Overall Length:** 0.215 inches **End Radius:** Between 0.010 inches and 0.030 inches **Taper Minor Diameter:** Between 2.972 inches and 2.982 inches **Taper Major Diameter:** 3.054 inches **Thread Size:** 3.750-32 Depth: 0.060 inches Bore Shape: **Tapered Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 30.0 **Beveled Thread:** Not included **Taper Major Diameter Location:** Drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

Not included

Bore Edge Process:

Rounded

Process End Location:

End opposite drive end

NSN 5365-01-246-4093

T252-d

Externally Threaded Ring - Page 2 of 2



Special Features:
Color black
Material:
$Aluminum\ alloy,\ qq-a-250/12,\ t651\ or\ qq-a-250/13,\ t651\ or\ qq-a-250/18,\ t651\ or\ qq-a-250/26,\ t651$
Material:
$Aluminum\ alloy,\ qq-a-250/12,\ t651\ or\ qq-a-250/13,\ t651\ or\ qq-a-250/18,\ t651\ or\ qq-a-250/26,\ t651\ or\ qq-a-250/2$
Surface Treatment:
Anodize
Surface Treatment:
Anodized, mil-a-8625
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: