NSN 5365-01-252-9646

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-252-9646

Thread Class:
3a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened

Between 0.180 inches and 0.200 inches

Overall Length:

Between 1.276 inches and 1.284 inches

Thread Size:

3.000-16

Width:

Bore Diameter:

Between 2.470 inches and 2.490 inches

Depth:

Between 0.290 inches and 0.310 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Unj

Drive Type:

Externally slotted

Material Hardness Rating:

Between 32.0 rockwell c and 38.0 rockwell c

Accommodation Type And Quantity:

6 slots

Angle Between Accommodations In Deg:

60.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Id has cbore 2.650 in. Diameter x 0.550 in. Dp; end opposite drive end has 2.820-2.830 in. Od, has 8 eq sp holes through od wall 0.375 in.

Dia; 21 grooves on drive edge

Material:

Steel, ams 6322 or steel, ams 6323

Material:

Steel comp 8740 or steel comp 8740

Shelf Life:

N/a

NSN 5365-01-252-9646

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d