

View Online at <https://aerobasegroup.com/nsn/5365-01-273-6488>

Overall Length:

Between 1.420 inches and 1.480 inches

Overall Width:

Between 1.370 inches and 1.430 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.710 inches and 0.770 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.800 inches and 0.860 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.300 inches and 0.360 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.290 inches and 0.350 inches

Bolt Hole Quantity:

4

End Application:

Rotary actuator/installation, f-16c/d common

Construction:

One-piece

Special Features:

8two holes 0.240 in. Min and 0.260in. Maximum on one side and two holes 0.302 in. Min and 0.322 in. Maximum on opposite side; tab 0.190 in. Min and 0.210 in. Maximum along length and 1.420 in. Min and 1.430 in. Maximum along width with 0.06 in bend, 30 degree radius

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 3 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07000

Mil-std (military Standard):

Mil-c-5541 spec.