

View Online at <https://aerobasegroup.com/nsn/5365-01-273-6490>

**Overall Length:**

Between 1.420 inches and 1.480 inches

**Overall Width:**

Between 0.830 inches and 0.890 inches

**Overall Thickness:**

Between 0.010 inches and 0.014 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 0.800 inches and 0.860 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.400 inches and 0.460 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.290 inches and 0.350 inches

**End Application:**

Rotary actuator/installation, f-16c/d common

**Construction:**

One-piece

**Special Features:**

One hole 0.240 in. Min and 0.260 in. Maximum on one end and one hole 0.302 in. Min and 0.322 in. Maximum on opposite end; tab 0.190 in. Min and 0.210 in. Maximum along length and 0.830 in. Min and 0.890 in. Maximum along width with 0.06 in. Bend, 30 degree radius

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07000

**Mil-std (military Standard):**

Mil-c-5541 spec.