NSN 5365-01-273-8408

Mil-std (military Standard):

Mil-c-5541 spec.



Shim - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5365-01-273-8408 **Overall Length:** Between 1.970 inches and 2.030 inches **Overall Width:** Between 1.830 inches and 1.890 inches Center To Center Distance Between Bolt Holes Along Width: Between 0.890 inches and 0.950 inches Center To Center Distance Between Bolt Holes Along Length: Between 0.950 inches and 1.010 inches **Outside Edge To Bolt Hole Center Distance Along Width:** Between 0.440 inches and 0.500 inches **Outside Edge To Bolt Hole Center Distance Along Length:** Between 0.350 inches and 0.410 inches **Bolt Hole Quantity:** 4 **End Application:** Rotary actuator/installation, f-16c/d common Construction: One-piece **Special Features:** 8two holes 0.302 in. Min and 0.322in. Maximum on one side and two holes 0.365 in. Min and 0.385 in. Maximum on opposite end; tab 0.190 in. Min and 0.210 in. Maximum along length and 1.830 in. Min and 1.890 in. Maximum along width with 0.06 in. Bend, 30 degree radius Material: Aluminum alloy 6061 **Material Specification:** Qq-a-250/11 federal specification single material response **Surface Treatment:** Chromate **Surface Treatment Specification:** Mil-c-5541, class 3 military specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A07000