Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-01-274-0165



Т	Thread Class:
	2a
Т	Thread Direction:
	Right-hand
	Casehardening Indicator:
	Not casehardened
C	Chamfer Angle In Deg:
	15.0
C	Chamfer Length:
	0.120 inches
V	Vidth:
E	Between 0.064 inches and 0.075 inches
C	Overall Length:
С	0.180 inches
Т	Thread Size:
С	0.750-16
E	Bore Diameter:
С	0.380 inches
C	Depth:
E	Between 0.046 inches and 0.070 inches
E	Bore Shape:
S	Straight
S	Screw Thread Series Designator:
ι	Jnf
C	Drive Type:
S	Slotted face
A	Accommodation Type And Quantity:
2	2 slots
A	Angle Between Accommodations In Deg:
1	80.0
E	Beveled Thread:
Ν	Not included
E	Bore Annular Internal Serration:
Ν	Not included
S	Setscrew Locking Notch:
Ν	Not included
E	Bore Edge Process:
C	Chamfered
F	Process End Location:
C	Drive end
N	Naterial:
S	Steel, qq-s-763, class 304, cond a

NSN 5365-01-274-0165

Externally Threaded Ring - Page 2 of 2

Material:

Steel comp 304

Surface Treatment:

Passivate

Surface Treatment:

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

