# NSN 5365-01-274-3273

Shim - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-274-3273

# **Overall Length:**

Between 1.420 inches and 1.480 inches

# **Overall Width:**

Between 1.370 inches and 1.430 inches

# Center To Center Distance Between Bolt Holes Along Width:

Between 0.710 inches and 0.770 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.800 inches and 0.860 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.300 inches and 0.360 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.290 inches and 0.350 inches

Bolt Hole Quantity:

4

**End Application:** 

Rotary actuator/installation, f-16c/d common

#### **Construction:**

One-piece

# **Special Features:**

Two holes 0.240 in. Min and 0.260 in. Maximum on one side and two holes 0.302 in. Min and 0.322 in. Maximum on opposite side; tab 0.190 in. Min and 0.210 in. Maximum along length and 1.420 in. Min and 1.430 in. Maximum along width with 0.06 in. Bend, 30 degree radius

#### Material:

Aluminum alloy 6061

# **Material Specification:**

Qq-a-250/11 federal specification single material response

#### Surface Treatment:

Chromate

# Surface Treatment Specification:

Mil-c-5541, class 3 military specification single treatment response

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### **Demilitarization:**

No

# Fiig:

A07000

# Mil-std (military Standard):

Mil-c-5541 spec.