

View Online at <https://aerobasegroup.com/nsn/5365-01-274-5411>

**Overall Length:**

Between 1.970 inches and 2.030 inches

**Overall Width:**

Between 1.830 inches and 1.890 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.890 inches and 0.950 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 0.950 inches and 1.010 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.440 inches and 0.500 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.350 inches and 0.410 inches

**Bolt Hole Quantity:**

4

**End Application:**

Rotary actuator/installation, f-16c/d common

**Construction:**

One-piece

**Special Features:**

8two holes 0.302 in. Min and 0.322in. Maximum on one side and two holes 0.365 in. Min and 0.385 in. Maximum on opposite end; tab 0.190 in. Min and 0.210 in. Maximum along length and 1.830 in. Min and 1.890 in. Maximum along width with 0.06 in. Bend, 30 degree radius

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07000

**Mil-std (military Standard):**

Mil-c-5541 spec.