

View Online at <https://aerobasegroup.com/nsn/5365-01-274-6121>

**Hole Diameter:**

Between 0.240 inches and 0.260 inches

**Overall Length:**

Between 1.470 inches and 1.530 inches

**Overall Width:**

Between 1.350 inches and 1.410 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.710 inches and 0.770 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 0.710 inches and 0.770 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.290 inches and 0.350 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.350 inches and 0.410 inches

**Bolt Hole Quantity:**

4

**End Application:**

Rotary actuator/installation, f-16c/d common

**Construction:**

One-piece

**Special Features:**

Tab 0.190 in. Min and 0.210 in. Maximum along length and 1.350 in. Min and 1.410 in. Maximum along width with 0.06 in. Bend, 30 degree radius

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Style Designator:**

Non-circular w/bolt holes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07000

**Mil-std (military Standard):**

Mil-c-5541 spec.