NSN 5365-01-304-7189

Nonmetallic Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-304-7189

| Nonmetallic Hardness Rating: |
|--|
| 30.0 shore durometer a and 40.0 shore durometer a |
| Overall Length: |
| 0.750 inches |
| Body Diameter: |
| 0.380 inches |
| Center Hole Diameter: |
| 0.250 inches |
| Design Type: |
| Single centrally located hole and split |
| Criticality Code Justification: |
| Feat Control of the C |
| Special Features: |
| tems are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us |
| navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the |
| successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, |
| olerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance |
| representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts; testing |
| aw mil-m-19595 |
| Material: |
| Rubber |
| Style Designator: |
| Round |
| Fsc Application Data: |
| Mk 16 mod 0 eod uba |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A535j0 |
| |
| |