## NSN 5365-01-315-5005

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-315-5005 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 15.0 **Chamfer Length:** 0.025 inches **Overall Length:** Between 0.860 inches and 0.870 inches Diameter: 0.188 inches **End Radius:** 0.030 inches **Thread Size:** 0.112-20 **Bore Diameter:** Between 3.254 inches and 3.256 inches Depth: 0.250 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.010 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

Chamfered

**Bore Edge Process:** 

## NSN 5365-01-315-5005

Externally Threaded Ring - Page 2 of 2



| Process End Location:                                    |
|----------------------------------------------------------|
| End opposite drive end                                   |
| Material:                                                |
| Phosphor bronze, qq-b-750                                |
| Material:                                                |
| Copper alloy 510 or copper alloy 524 or copper alloy 544 |
| Shelf Life:                                              |
| N/a                                                      |
| Unit Of Measure:                                         |
|                                                          |
| Demilitarization:                                        |
| No                                                       |

Fiig: T252-d