

View Online at <https://aerobasegroup.com/nsn/5365-01-316-9149>

Thread Direction:

Right-hand

Counterbore Diameter:

1.188 inches

Counterbore Depth:

0.625 inches

Overall Length:

1.250 inches

Thickness:

0.250 inches

Wrenching Facility Shape:

Hexagon

Screw Thread Length:

0.812 inches

Width Across Flats:

1.656 inches

Counterbore Location:

Threaded end

Hole Inside Diameter:

Between 0.938 inches and 0.968 inches

Features Provided:

Counterbore

Thready Qty Per Inch (tpi):

16

Thread Size:

1.4375 inches

Material:

Steel comp 1117 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

Material Specification:

Aisi 1117 assn standard single material response or aisi 1015 assn standard single material response or aisi 1016 assn standard single material response or aisi 1017 assn standard single material response or aisi 1018 assn standard single material response or aisi 1019 assn standard single material response or aisi 1020 assn standard single material response or aisi 1021 assn standard single material response or aisi 1022 assn standard single material response or aisi 1023 assn standard single material response or aisi 1025 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Dod-p-16232, type m, class 1 military specification single treatment response

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

Fig:

A540s0

Mil-std (military Standard):

spec.