

View Online at <https://aerobasegroup.com/nsn/5365-01-316-9149>

**Thread Direction:**

Right-hand

**Counterbore Diameter:**

1.188 inches

**Counterbore Depth:**

0.625 inches

**Overall Length:**

1.250 inches

**Thickness:**

0.250 inches

**Wrenching Facility Shape:**

Hexagon

**Screw Thread Length:**

0.812 inches

**Width Across Flats:**

1.656 inches

**Counterbore Location:**

Threaded end

**Hole Inside Diameter:**

Between 0.938 inches and 0.968 inches

**Features Provided:**

Counterbore

**Thready Qty Per Inch (tpi):**

16

**Thread Size:**

1.4375 inches

**Material:**

Steel comp 1117 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

**Material Specification:**

Aisi 1117 assn standard single material response or aisi 1015 assn standard single material response or aisi 1016 assn standard single material response or aisi 1017 assn standard single material response or aisi 1018 assn standard single material response or aisi 1019 assn standard single material response or aisi 1020 assn standard single material response or aisi 1021 assn standard single material response or aisi 1022 assn standard single material response or aisi 1023 assn standard single material response or aisi 1025 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Dod-p-16232, type m, class 1 military specification single treatment response

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

A540s0

**Mil-std (military Standard):**

spec.