NSN 5365-01-317-2671

Shim - Page 1 of 1



Outside Diameter: Between 0.730 inches and 0.770 inches Aperture Diameter: Between 0.530 inches and 0.540 inches End Application: 2520-01-089-5011 Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 1084 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life: N/a	
Aperture Diameter: Between 0.530 inches and 0.540 inches End Application: 2520-01-089-5011 Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Between 0.530 inches and 0.540 inches End Application: 2520-01-089-5011 Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
End Application: 2520-01-089-5011 Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
2520-01-089-5011 Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Construction: One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
One-piece Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Hardness Rating: Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Between 77.0 rockwell superficial 15-n and 86.0 rockwell superficial 15-n Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Material: Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 108 Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Material Specification: Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	
Astm a682 assn standard single material response Style Designator: Circular Shelf Life:	6
Style Designator: Circular Shelf Life:	
Circular Shelf Life:	
Shelf Life:	
N/a	
. 40	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A07000	