Machine Thread Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-328-8067

| Thread Direction: |
|---|
| Right-hand |
| Counterbore Diameter: |
| 0.650 inches |
| Overall Length: |
| Between 0.740 inches and 0.750 inches |
| Diameter: |
| 1.000 inches |
| Thickness: |
| Between 0.099 inches and 0.100 inches |
| Wrenching Facility Shape: |
| Round |
| Screw Thread Length: |
| 0.220 inches |
| Counterbore Location: |
| Threaded end |
| Hole Inside Diameter: |
| Between 0.4995 inches and 0.5010 inches |
| Features Provided: |
| Counterbore |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.750 inches |
| Material: |
| Steel |
| Material Specification: |
| Ams 5643 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Eile. |
| Fiig: |
| A540s0 |