## NSN 5365-01-335-7193

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-335-7193

| Overall | Length: |
|---------|---------|
|         |         |

Between 1.9050 inches and 1.9150 inches

Flange Outside Diameter:

Between 1.1750 inches and 1.1850 inches

Flange Width:

Between 0.8800 inches and 0.9000 inches

Left Internal Flange Hole Diameter:

Between 0.2000 inches and 0.2100 inches

Left Internal Flange Width:

0.0900 inches

**Right Internal Flange Width:** 

0.4200 inches

**Interior Flange Hole Diameter:** 

Between 0.8950 inches and 0.9050 inches

**End To Flange Distance:** 

Between 0.3550 inches and 0.3650 inches

**Corner Shape:** 

Square all corners

Left End Body Diameter:

Between 0.9808 inches and 0.9814 inches

**Right End Body Diameter:** 

Between 0.9900 inches and 1.0100 inches

Material:

Aluminum alloy 6061

**Material Specification:** 

Qq-a-200/8 federal specification single material response or qq-a-225/8 federal specification single material response or qq-a-250/11, t6 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1 or 2 military specification single treatment response

**Style Designator:** 

21c-3 solid, external flange, internal flange at both ends

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-a-8625 spec.