## NSN 5365-01-348-2967

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-348-2967 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.375 inches and 0.380 inches **Overall Length:** Between 1.126 inches and 1.136 inches **Thread Size:** 2.750-12 **Bore Diameter:** Between 2.245 inches and 2.255 inches Depth: 0.175 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unj **Drive Type:** Slotted face **Material Hardness Rating:** Between 35.0 rockwell c and 42.0 rockwell c **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 4 holes 0.055 in. Dia, equally spaced between slots and perpendicular to axis Material: Steel, ams 5659

Material:

Steel comp xm-12

## NSN 5365-01-348-2967

Externally Threaded Ring - Page 2 of 2



C		T	4	4 -
Sun	ace	Trea	une	HIT.

Cadmium and chromate

**Surface Treatment:** 

Cadmium, qq-p-416, type 2, class 2

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d