# NSN 5365-01-351-1484

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-351-1484

# Thread Pitch Diameters:

+2.2250/+2.5050 inches

# **Thread Direction:**

**Right-hand** 

# Countersink Angle In Deg:

45.0

### **Overall Length:**

1.750 inches

### Diameter:

Between 3.613 inches and 3.637 inches

Thickness:

0.750 inches

### Wrenching Facility Shape:

Knurled

### **Countersink Depth:**

# 0.090 inches

### Screw Thread Length:

0.500 inches

#### **Countersink Location:**

Wrenching end

# Hole Inside Diameter:

0.640 inches

# Features Provided:

Countersunk

# Thready Qty Per Inch (tpi):

5

# Material:

Aluminum alloy 6061

### **Material Specification:**

Qq-a-200/8, t6 federal specification single material response or qq-a-225/8, t6 federal specification single material response

### Surface Treatment:

Anodize

### Surface Treatment Specification:

Mil-a-8625, type 3, class 1 military specification single treatment response

# Thread Series Designator:

Buttress

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5365-01-351-1484

Machine Thread Bushing - Page 2 of 2



Fiig: A540s0

Mil-std (military Standard):

Mil-a-8625 spec.