## NSN 5365-01-358-1729

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-358-1729

| Overall Length: Between 0.8075 inches and 0.8175 inches  Body Outside Diameter: Between 0.4850 inches and 0.5150 inches  Body Inside Diameter: Between 0.3770 inches and 0.4270 inches  Corner Shape: Square all corners  Special Features: Gray anodize  Material: Aluminum alloy 2024  Material Specification: Ww-t-700/3, ty1, 13 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment: Anodize  Sturface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response  Style Designator: 17c solid, plain, no outside flanges  Specification Data: 80205-nas43 professional/industrial association standard  Shelf Life: N/a  Unit Of Measure: |              |
|---|--------------|
| Between 0.4850 inches and 0.5150 inches  Body Inside Diameter:  Between 0.3770 inches and 0.4270 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life: N/a  |              |
| Between 0.4850 inches and 0.5150 inches  Body Inside Diameter:  Between 0.3770 inches and 0.4270 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life: N/a  |              |
| Between 0.3770 inches and 0.4270 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment: Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life: N/a  |              |
| Between 0.3770 inches and 0.4270 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a   |              |
| Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a   |              |
| Square all corners  Special Features: Gray anodize  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment: Anodize  Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response  Style Designator: 17c solid, plain, no outside flanges  Specification Data: 80205-nas43 professional/industrial association standard  Shelf Life: N/a  |              |
| Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a  |              |
| Gray anodize  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo  Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a   |              |
| Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo Surface Treatment:  Anodize Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response Style Designator:  17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a  |              |
| Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material respo Surface Treatment:  Anodize Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response Style Designator:  17c solid, plain, no outside flanges Specification Data:  80205-nas43 professional/industrial association standard Shelf Life: N/a  |              |
| Material Specification:  Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a   |              |
| Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize  Surface Treatment Specification:  Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a   |              |
| Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a  |              |
| Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a   | ial response |
| Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a   |              |
| Mil-a-8625, ty1 military specification single treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a  |              |
| Style Designator:  17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard  Shelf Life:  N/a  |              |
| 17c solid, plain, no outside flanges  Specification Data: 80205-nas43 professional/industrial association standard  Shelf Life: N/a   |              |
| Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a  |              |
| 80205-nas43 professional/industrial association standard  Shelf Life: N/a   |              |
| Shelf Life:<br>N/a  |              |
| N/a   |              |
|   |              |
| Unit Of Measure:  |              |
|   |              |
|   |              |
| Demilitarization:   |              |
| No  |              |
| Fiig:   |              |
| A045a0  |              |
| Mil-std (military Standard):  |              |
| Mil-a-8625 spec.  |              |