NSN 5365-01-399-2192

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-399-2192

| Overall Length: Between 2.1981 inches and 2.2081 inches Body Outside Diameter: Between 0.4850 inches and 0.5250 inches Body Inside Diameter: Between 0.3770 inches and 0.4270 inches Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: | |
|--|---|
| Between 0.4850 inches and 0.5250 inches Body Inside Diameter: Between 0.3770 inches and 0.4270 inches Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, 13 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Between 0.4850 inches and 0.5250 inches Body Inside Diameter: Between 0.3770 inches and 0.4270 inches Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | 2.2081 inches |
| Body Inside Diameter: Between 0.3770 inches and 0.4270 inches Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Between 0.3770 inches and 0.4270 inches Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | 0.5250 inches |
| Corner Shape: Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Square all corners Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | 0.4270 inches |
| Special Features: Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Gray anodize Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Material Specification: Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Ww-t-700/3, ty1, t3 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | ecification single material response or qq-a-225/6, t4 federal specification single material response |
| Surface Treatment Specification: Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Mil-a-8625, ty1 military specification single treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| Style Designator: 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | ation: |
| 17c solid, plain, no outside flanges Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | ication single treatment response |
| Specification Data: 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | |
| 80205-nas43 professional/industrial association standard Shelf Life: N/a Unit Of Measure: | anges |
| Shelf Life: N/a Unit Of Measure: | |
| N/a Unit Of Measure: | lustrial association standard |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Demilitarization: | |
| | |
| No | |
| Fiig: | |
| A045a0 | |
| Mil-std (military Standard): | |
| Mil-a-8625 spec. | |