NSN 5365-01-413-2658

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-413-2658 **Thread Direction:** Right-hand **Counterbore Diameter:** Between 4.580 inches and 4.610 inches **Counterbore Depth:** 0.610 inches **Overall Length:** Between 4.080 inches and 4.120 inches Diameter: Between 6.250 inches and 6.280 inches **Wrenching Facility Shape:** Round **Screw Thread Length:** 2.750 inches **Counterbore Location:** Threaded end **Hole Inside Diameter:** Between 5.000 inches and 5.010 inches **Features Provided:** Counterbore Thready Qty Per Inch (tpi): 2 **Thread Size:** 5.750 inches **Special Features:** Has four equally spaced threaded holes (0.375-16unc-2b) on wrenching end; has four equally spaced threaded holes (0.164-32unc-3b) on threaded end; has one unthreaded hole with diameter of 0.120 in. And diameter of 0.130 in. On wrenching end; has four unthreaded holes with diameter of 0.290 in. And diameter of 0.300 in. Along threaded sides. Material: Aluminum alloy 6061 **Material Specification:** Alloy 6061, t6 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 3, class 1 military specification single treatment response **Thread Series Designator:** Acme Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5365-01-413-2658

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0

Mil-std (military Standard):

Mil-a-8625 spec.