

View Online at <https://aerobasegroup.com/nsn/5365-01-436-4080>

**Hole Diameter:**

Between 0.146 inches and 0.152 inches

**Overall Length:**

Between 1.790 inches and 1.810 inches

**Overall Width:**

Between 0.665 inches and 0.685 inches

**Inside Corner Radius:**

0.015 inches

**Aperture Width:**

Between 0.198 inches and 0.202 inches

**Aperture Length:**

Between 0.898 inches and 0.902 inches

**Overall Thickness:**

0.020 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.288 inches and 0.308 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.490 inches and 1.510 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.179 inches and 0.199 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.140 inches and 0.160 inches

**Bolt Hole Quantity:**

4

**End Application:**

F-15i

**Outside Edge To Inside Edge Smallest Distance Along Width:**

Between 0.237 inches and 0.239 inches

**Outside Edge To Inside Edge Smallest Distance Along Length:**

Between 0.449 inches and 0.451 inches

**Special Features:**

Mask all mating surfaces and holes; epoxy prime coat only outside edges of spacer per rpr17003 type i or ii; outside corners are chamfered  
0.100 in. X 45.0 deg

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t4 federal specification single material response or qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

**Style Designator:**

Non-circular w/bolt holes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07000

**Mil-std (military Standard):**

Mil-c-5541 spec.