

View Online at <https://aerobasegroup.com/nsn/5365-01-436-4085>

Hole Diameter:

Between 0.146 inches and 0.152 inches

Overall Length:

Between 1.790 inches and 1.810 inches

Overall Width:

Between 0.665 inches and 0.685 inches

Inside Corner Radius:

0.015 inches

Aperture Width:

Between 0.198 inches and 0.202 inches

Aperture Length:

Between 0.898 inches and 0.902 inches

Overall Thickness:

0.188 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.288 inches and 0.308 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.490 inches and 1.510 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.179 inches and 0.199 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.140 inches and 0.160 inches

Bolt Hole Quantity:

4

End Application:

F-15i

Outside Edge To Inside Edge Smallest Distance Along Width:

Between 0.237 inches and 0.239 inches

Outside Edge To Inside Edge Smallest Distance Along Length:

Between 0.449 inches and 0.451 inches

Special Features:

Mask all mating surfaces and holes; epoxy prime coat only outside edges of spacer per rpr17003 type i or ii; outside corners are chamfered

0.100 in. X 45.0 deg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response or qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Non-circular w/bolt holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07000

Mil-std (military Standard):

Mil-c-5541 spec.