

View Online at <https://aerobasegroup.com/nsn/5365-01-445-1422>

**Overall Length:**

Between 0.620 inches and 0.630 inches

**Body Outside Diameter:**

Between 0.995 inches and 1.005 inches

**Body Inside Diameter:**

Between 0.312 inches and 0.317 inches

**End Application:**

P/n 176370; f15-i acct

**First Left Counterbore Depth:**

Between 0.585 inches and 0.595 inches

**Second Left Counterbore Depth:**

Between 0.030 inches and 0.040 inches

**First Right Step Width:**

Between 0.160 inches and 0.170 inches

**Second Right Step Width:**

Between 0.355 inches and 0.365 inches

**Product Name:**

Bushing, safety switch

**First Left Counterbore Inside Diameter:**

Between 0.386 inches and 0.396 inches

**First Right Step Outside Diameter:**

Between 0.495 inches and 0.505 inches

**Second Right Step Outside Diameter:**

Between 0.745 inches and 0.755 inches

**Special Features:**

0.123 in. Min, 0.128 in. Max, drill, csink 100 degrees, 0.225 in. Min, 0.240 in. Maximum dia-2 pl; 0.142 in. Min, 0.147 in. Maximum diameter through hole-2 pl

**Material:**

Steel comp 416 or steel comp 630

**Material Specification:**

Astma582 assn standard single material response or ams5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Style Designator:**

Stepped spacer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07000