

View Online at <https://aerobasegroup.com/nsn/5365-01-445-1422>

Overall Length:

Between 0.620 inches and 0.630 inches

Body Outside Diameter:

Between 0.995 inches and 1.005 inches

Body Inside Diameter:

Between 0.312 inches and 0.317 inches

End Application:

P/n 176370; f15-i acct

First Left Counterbore Depth:

Between 0.585 inches and 0.595 inches

Second Left Counterbore Depth:

Between 0.030 inches and 0.040 inches

First Right Step Width:

Between 0.160 inches and 0.170 inches

Second Right Step Width:

Between 0.355 inches and 0.365 inches

Product Name:

Bushing, safety switch

First Left Counterbore Inside Diameter:

Between 0.386 inches and 0.396 inches

First Right Step Outside Diameter:

Between 0.495 inches and 0.505 inches

Second Right Step Outside Diameter:

Between 0.745 inches and 0.755 inches

Special Features:

0.123 in. Min, 0.128 in. Max, drill, csink 100 degrees, 0.225 in. Min, 0.240 in. Maximum dia-2 pl; 0.142 in. Min, 0.147 in. Maximum diameter through hole-2 pl

Material:

Steel comp 416 or steel comp 630

Material Specification:

Astma582 assn standard single material response or ams5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Style Designator:

Stepped spacer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07000