## NSN 5365-01-457-9919

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-457-9919 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Diameter: Between 0.097 inches and 0.100 inches **Thread Size:** 1.250 **Bore Diameter:** 0.831 inches Depth: 0.094 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 0.484 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Criticality Code Justification:** Zzzy Material: **Brass** Material: Copper alloy

**Special Test Features:** 

Special quality control testing

## NSN 5365-01-457-9919

Externally Threaded Ring - Page 2 of 2



## **Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Reference Number Differentiating Characteristics:**

As differentiated by m	naterial which n	nust conform to	ships parts contro	l center special	quality control	provisions
------------------------	------------------	-----------------	--------------------	------------------	-----------------	------------

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

T252-d