NSN 5365-01-485-4535

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-485-4535

| view Online at https://aerobasegroup.com/nsn/5365-01-465-4535 |
|---|
| Overall Length: |
| Between 3.7490 inches and 3.7510 inches |
| Body Outside Diameter: |
| Between 0.4900 inches and 0.5100 inches |
| Body Inside Diameter: |
| Between 0.3800 inches and 0.3840 inches |
| End Application: |
| C-130 aircraft |
| Left Flange Outside Diameter: |
| Between 0.7150 inches and 0.7250 inches |
| Right Flange Outside Diameter: |
| Between 0.7150 inches and 0.7250 inches |
| Left Flange Width: |
| Between 0.0500 inches and 0.0700 inches |
| Right Flange Width: |
| Between 0.0500 inches and 0.0700 inches |
| Corner Shape: |
| Square outside right corner |
| Special Features: |
| T.O. 1a-10a-4-27, fig 10, index 24 |
| Material: |
| Aluminum alloy 7075 |
| Material Specification: |
| Qq-a-200/11 federal specification single material response or qq-a-225/9 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military standard single treatment response |
| Style Designator: |
| 18c solid, external flanges both ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| |

Mil-a-8625 spec.

Mil-std (military Standard):