## NSN 5365-01-506-6193

Plate Spacer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-506-6193

## Hole Diameter:

Between 0.421 inches and 0.428 inches

## **Overall Length:**

5.500 inches

## **Overall Width:**

5.250 inches

## **Overall Thickness:**

0.125 inches

## **Outside Corner Bevel Length Along Width:**

0.250 inches

## **Outside Corner Bevel Length Along Length:**

## 0.250 inches

Center To Center Distance Between Bolt Holes Along Width:

## 4.380 inches

Center To Center Distance Between Bolt Holes Along Length:

## 3.750 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.440 inches

Outside Edge To Bolt Hole Center Distance Along Length:

1.060 inches

## **Bolt Hole Quantity:**

4

## **End Application:**

An/spn-43c fc; next assembly 193641-1

## **Product Name:**

Spacer, servo pedestal

## Material:

Aluminum alloy 6061

## **Material Specification:**

Qq-a-250 assn standard single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

## Style Designator:

Non-circular w/bolt holes

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5365-01-506-6193

Plate Spacer - Page 2 of 2

**Fiig:** A07000

Mil-std (military Standard):

Mil-c-5541 spec.

