

View Online at <https://aerobasegroup.com/nsn/5365-01-521-0502>

**Hole Diameter:**

Between 0.374 inches and 0.381 inches

**Overall Length:**

Between 3.120 inches and 3.180 inches

**Overall Width:**

Between 1.720 inches and 1.780 inches

**Overall Thickness:**

Between 0.178 inches and 0.198 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.240 inches and 1.260 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.470 inches and 0.530 inches

**Bolt Hole Centerline To Nearest Edge Distance:**

Between 0.865 inches and 0.885 inches

**Bolt Hole Quantity:**

2

**Product Name:**

Spacer, support cylinder

**Material:**

Steel comp 1008

**Material Specification:**

Astm a108 assn standard single material response or astm 576 assn standard single material response

**Surface Treatment:**

Phosphate and plastic polyamide and plastic polyurethane

**Surface Treatment Specification:**

Dod-p-16232, type m, class 3 military specification 1st treatment response or dod-p-16232, type z, class 3 military specification 1st treatment response and mil-p-2337 type 1 military specification 2nd treatment response and mil-c-85285 type ii military specification 3rd treatment response

**Style Designator:**

Non-circular w/square corners

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07000

**Mil-std (military Standard):**

Mil-p-2337 spec.