

View Online at <https://aerobasegroup.com/nsn/5365-01-525-9383>

**Hole Diameter:**

Between 0.405 inches and 0.412 inches

**Overall Length:**

4.500 inches

**Overall Width:**

2.250 inches

**Overall Thickness:**

0.250 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.625 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.297 inches and 0.327 inches

**Bolt Hole Quantity:**

6

**End Application:**

Heavyweight engine housing maint, stand

**Product Name:**

Shim, swivel fixture

**Special Features:**

All measurements are taken after anodize finish; surface roughness- machined surfaces to be 125 underscore check mark in accordance with ansi/asma b46.1; center to center distance between bolt holes along length are not equal, one distance is 1.625 in, the second 1.375 in; the distance from the outside edge to bolt hole center along length is 0.500in and 1.000 in respectively; the outside corner bevel edge is 0.250 in x 45 degrees on each of four corners; part to be used on maintenace stand for an internal combustion engine used in a (heavyweight) or larger torpedo

**Material:**

Aluminum alloy 6061

**Material Specification:**

Alloy 6061-t6 astm b209 assn standard all material responses

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Sae ams-a-8625 assn standard all treatment responses

**Style Designator:**

Non-circular w/bolt holes

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07000