NSN 5365-01-534-4837

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-534-4837

Overall Length: Between 1.8856 inches and 1.8956 inches Body Outside Diameter: Between 0.6100 inches and 0.6400 inches Body Inside Diameter: Between 0.5170 inches and 0.5670 inches End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification single treatment response Style Designator: 17c solid, plain, no outside flanges Shelf Life:
Between 0.6100 inches and 0.6400 inches Body Inside Diameter: Between 0.5170 inches and 0.5670 inches End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Between 0.6100 inches and 0.6400 inches Body Inside Diameter: Between 0.5170 inches and 0.5670 inches End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Between 0.5170 inches and 0.5670 inches End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Between 0.5170 inches and 0.5670 inches End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
End Application: C17a acft Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Corner Shape: Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Square all corners Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Aluminum alloy 2024 Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Material Specification: Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Ww-t-700/3, ty i federal specification single material response or qq-a-225/6 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Anodize Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Surface Treatment Specification: Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Mil-a-8625, ty i military specification single treatment response Style Designator: 17c solid, plain, no outside flanges
Style Designator: 17c solid, plain, no outside flanges
17c solid, plain, no outside flanges
Shelf Life:

N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):
Mil-a-8625 spec.