

View Online at <https://aerobasegroup.com/nsn/5365-01-631-2267>

Slot Width:

Between 0.29 inches and 0.33 inches

Slot Length:

Between 0.61 inches and 0.65 inches

Overall Length:

Between 6.98 inches and 7.02 inches

Overall Width:

Between 0.98 inches and 1.02 inches

Overall Thickness:

Between 0.48 inches and 0.52 inches

End Application:

2355-01-549-5271

Slot Quantity:

2

Product Name:

Spacer, fire suppression bracket, digirack

Special Features:

Material is heat treated to -h32. Center-to-center distance between slots is 6.00 inches. Spacer has a 1.87 inch long recess that is .37 inches thick at one end.

Color:

Tan

Material:

Aluminum alloy 5052

Material Specification:

Astm b209 assn standard single material response

Surface Treatment:

Primer epoxy and carc (chemical agent resistant coating)

Surface Treatment Specification:

Mil-dtl-53022 military specification 1st treatment response or mil-dtl-53030 military specification 1st treatment response and mil-dtl-53039 type 3 military specification 2nd treatment response or mil-dtl-64159 type 2 military specification 2nd treatment response

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A556d0

Mil-std (military Standard):

Mil-dtl-53022 spec.