NSN 5365-01-632-4823

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-01-632-4823

Overall Length: 2.75 inches Body Outside Diameter: Between 2.5018 inches and 2.5023 inches Body Inside Diameter: 2.38 inches Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Body Outside Diameter: Between 2.5018 inches and 2.5023 inches Body Inside Diameter: 2.38 inches Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Between 2.5018 inches and 2.5023 inches Body Inside Diameter: 2.38 inches Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Body Inside Diameter: 2.38 inches Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
2.38 inches Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Flange Outside Diameter: Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Between 2.995 inches and 3.000 inches End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
End Application: Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Nuc equipment Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Flange Width: Between 0.242 inches and 0.252 inches Hardness Rating:	
Between 0.242 inches and 0.252 inches Hardness Rating:	
Hardness Rating:	
65.0 rockwell c outer layer	
Surface Groove Location And Quantity:	
5 internal	
Product Name:	
Upper spring housing bushing	
Special Features:	
Nitride steel parts. Hazardous material review performed iaw hazardous material minimization procedure revision 1. N	lo hazardous materials
are present in the items specified. Magnetic particle inspect all areas in accordance with mil-std-271f.	
Material:	
Steel	
Style Designator:	
Solid, external flange one end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A045a0	