Wood Line Construction Pole - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-161-2956

# Treatment Type:

Preservative, tt-w-571

### Frame Roof Type:

Flat or one way

## Preservative Solution Type:

Ammoniacal copper arsenite or chromated copper arsenate, type i, ii or iii or coal-tar creosote or pentachlorophenol

# Species-grade And Grading Association:

Cedar ungraded unrecognized or douglas fir ungraded unrecognized or larch ungraded unrecognized or pine ungraded unrecognized

## Gain Type And Quantity:

1 mortise or 1 slab

# Measuring Method And Length:

45.000 feet specified

## Typical Wood Products Use:

Communication and transmission lines, full length preservative treated, gained and bored for two standard crossarms

#### Service Usage:

Utility

### **Special Features:**

Tfor 2 standard 4.500 in. Crossarms, 2 holes drilled 0.688 in. Dia, spaced 24.000 in. Apart w/center of top hole 10.250 in. Porm 0.250 in.

From peak of roof, poles @shall be clean peeled, the american national standards institute class 1

### Supplementary Features:

Typical use--for communication and transmission lines, unit of issue--each

### **Specification Or Standard:**

1 class

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A173a0