

View Online at <https://aerobasegroup.com/nsn/5510-00-220-1537>

**Maximum Grain Slope:**

Any acceptable

**Random Width:**

5 in. And wider, per applicable association standard

**Species-grade And Grading Association:**

Douglas fir factory select western wood products association or douglas fir select shop west coast lumber inspection bureau or pine, eastern white factory select northern hardwood and pine manufacturers association or pine, idaho white factory select western wood products association or pine, ponderosa factory select western wood products association or pine, norway factory select northern hardwood and pine manufacturers association or pine, sugar factory select western wood products association or spruce, eastern factory select northern hardwood and pine manufacturers association or spruce, sitka select shop west coast lumber inspection bureau

**Moisture Content Retention Percentage:**

15.0

**Random Length:**

H ft and longer, permitting 25 pct 4-8 ft lengths

**Width-location And Measuring Method:**

5.000 inches random

**Measuring Method And Length:**

4.000 feet random

**Surface Condition Degree:**

Rough-unsanded full length

**Thickness-location And Measuring Method:**

1.000 inches specified

**Typical Wood Products Use:**

Cutting grade for remanufacturing purposes such as door and window stock, patterns, furniture and templates

**Supplementary Features:**

Unit of issue-board foot

**Specification Data:**

81348-mm-l-751 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A173a0