

View Online at <https://aerobasegroup.com/nsn/5510-00-220-1538>

Maximum Grain Slope:

Any acceptable

Random Width:

Per applicable assn std

Species-grade And Grading Association:

Douglas fir factory select western wood products association or douglas fir select shop west coast lumber inspection bureau or pine, eastern white factory select northern hardwood and pine manufacturers association or pine, idaho white factory select western wood products association or pine, ponderosa factory select western wood products association or pine, norway factory select northern hardwood and pine manufacturers association or pine, sugar factory select western wood products association or spruce, eastern factory select northern hardwood and pine manufacturers association or spruce, sitka select shop west coast lumber inspection bureau

Moisture Content Retention Percentage:

15.0

Random Length:

4 ft and longer, permitting 25 pct 4-8 ft

Width-location And Measuring Method:

5.000 inches random

Measuring Method And Length:

4.000 feet random

Surface Condition Degree:

Rough-unsanded full length

Thickness-location And Measuring Method:

1.250 inches specified

Typical Wood Products Use:

Cutting grade for remanufacturing purposes such as door and window stock, patterns, furniture and templates

Special Features:

Min 70 pct clear

Supplementary Features:

U/i-board foot

Specification Data:

81349-mm-l-751 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A173a0