NSN 5510-00-220-6110

Board Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-220-6110

Thickness-location And Measuring Method:

81348-mm-I-751 government specification

Temporary sheathing, dunnage, boxing and crating

1.000 inches specified

Typical Wood Products Use:

Supplementary Features:

Specification Or Standard:

U/i-board foot

lii table Shelf Life:

N/a

No Fiig: A173a0

Specification Data:

Unit Of Measure:

Demilitarization:

Species-grade And Grading Association:
Any acceptable 4 common northeastern lumber manufacturers association or any acceptable 4 common northern hardwood and pin
manufacturers association or any acceptable 4 common western wood products association or any acceptable standard northeastern
lumber manufacturers association or any acceptable utility west coast lumber inspection bureau or pine, southern no. 3 boards sou
pine inspection bureau or redwood merchantable redwood inspection service
Moisture Content Retention Percentage:
19.0
Random Length:
6 ft and longer, w/ maximum of 10 pct 6-9 ft, min of 30 pct 14 ft and longer
Width-location And Measuring Method:
4.000 inches specified
Measuring Method And Length:
6.000 feet random
Surface Condition Degree:
Surfaced four sides