NSN 5510-00-220-6144

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-220-6144

Surface Condition Degree:

Thickness-location And Measuring Method:

81348-mm-l-751 government specification

Light framing for high quality construction, studs and roof trusses

Surfaced four sides

2.000 inches specified

Typical Wood Products Use:

Supplementary Features:

Specification Or Standard:

U/i-board foot

3 table Shelf Life:

N/a

No Fiig: A173a0

Specification Data:

Unit Of Measure:

Demilitarization:

Species-grade And Grading Association:
Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable no. 1 northern hardwood and pine manufacturers
association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable no. 1 western wood products association or
any acceptable construction northeastern lumber manufacturers association or any acceptable construction northern hardwood and pine
manufacturers association or any acceptable construction west coast lumber inspection bureau or any acceptable construction western
wood products association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection
oureau or redwood no. 1 redwood inspection service or redwood construction redwood inspection service
Moisture Content Retention Percentage:
19.0
Random Length:
6 ft and longer, w/ maximum of 10 pct 6-9 ft, min of 40 pct 14 ft and longer
Width-location And Measuring Method:
3.000 inches specified
Measuring Method And Length:
5.000 feet random