

View Online at <https://aerobasegroup.com/nsn/5510-00-220-6144>

**Species-grade And Grading Association:**

Any acceptable no. 1 northeastern lumber manufacturers association or any acceptable no. 1 northern hardwood and pine manufacturers association or any acceptable no. 1 west coast lumber inspection bureau or any acceptable no. 1 western wood products association or any acceptable construction northeastern lumber manufacturers association or any acceptable construction northern hardwood and pine manufacturers association or any acceptable construction west coast lumber inspection bureau or any acceptable construction western wood products association or pine, southern no. 1 southern pine inspection bureau or pine, southern construction southern pine inspection bureau or redwood no. 1 redwood inspection service or redwood construction redwood inspection service

**Moisture Content Retention Percentage:**

19.0

**Random Length:**

6 ft and longer, w/ maximum of 10 pct 6-9 ft, min of 40 pct 14 ft and longer

**Width-location And Measuring Method:**

3.000 inches specified

**Measuring Method And Length:**

6.000 feet random

**Surface Condition Degree:**

Surfaced four sides

**Thickness-location And Measuring Method:**

2.000 inches specified

**Typical Wood Products Use:**

Light framing for high quality construction, studs and roof trusses

**Supplementary Features:**

U/i-board foot

**Specification Data:**

81348-mm-l-751 government specification

**Specification Or Standard:**

3 table

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A173a0