NSN 5510-00-220-6194

Dimension Softwood Lumber - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5510-00-220-6194

Surface Condition Degree:

Thickness-location And Measuring Method:

81348-mil-I-751 government specification

Ordinary construction, boxes, studs, rafters and blocking

Surfaced four sides

2.000 inches specified

Typical Wood Products Use:

Supplementary Features:

Specification Or Standard:

Unit of issue bf

lii table Shelf Life:

N/a

No Fiig: A173a0

Specification Data:

Unit Of Measure:

Demilitarization:

Species-grade And Grading Association:
Any acceptable no. 2 northeastern lumber manufacturers association or any acceptable standard northeastern lumber manufacturers
association or any acceptable no. 2 northern hardwood and pine manufacturers association or any acceptable standard northern hardwood
and pine manufacturers association or any acceptable no. 2 west coast lumber inspection bureau or any acceptable standard west coast
lumber inspection bureau or any acceptable no. 2 western wood products association or any acceptable standard western wood products
association or pine, southern no. 2 southern pine inspection bureau or pine, southern standard southern pine inspection bureau or
redwood no. 2 redwood inspection service or redwood standard redwood inspection service
Moisture Content Retention Percentage:
19.0
Random Length:
6 ft and longer, w/a maximum of 10% to be 6-9 ft and min of 40% 14 ft and longer
Width-location And Measuring Method:
4.000 inches specified
Measuring Method And Length:
6.000 feet random